



# HSM V-Press 860 plus QL

## Vertikale Ballenpresse HSM V-Press 860 plus QL

Die HSM V-Press 860 ist mit einer Presskraft von 594 kN und einer geräuscharmen und Energie sparenden Technologie die wirtschaftliche und umweltgerechte Lösung für Ihre Entsorgungsaufgaben.

### Technical data

<b>Order number:</b>	6048217A	<b>Bale length x Bale width x Bale height:</b>	1200 x 1000 x 780 mm
<b>EAN</b>	4026631080118	<b>Bale weight:</b>	430 kg
<b>Pressing power:</b>	594 kN	<b>Method of loading:</b>	manual
<b>Specific pressing power:</b>	63,46 N/cm <sup>2</sup>	<b>Noise level (idle operation):</b>	ca. 68 dB(A)
<b>Driving power:</b>	4 kW	<b>Width x Depth x Height:</b>	1797 x 1314 x 2990 mm
<b>Voltage / Frequency:</b>	400 V / 50 Hz	<b>Weight:</b>	2200 kg
<b>Cycle time when idling vacío:</b>	25 s	<b>Related product line:</b>	V-Press
<b>Volume throughput in idle operation (theor.):</b>	26,25 m <sup>3</sup> /h	<b>Type of consumables:</b>	Quick link wire
<b>Loading height:</b>	1110 mm	<b>Press material:</b>	Mixed paper, Cardboard
<b>Loading aperture width x height:</b>	1195 x 650 mm		

### Product information



To fill the press, the upper half of the doors is pushed down and automatically opens after the compression process



Hand wheel door lock - Easy to handle thanks to counter-rotating thread for quick opening and closing



The HSM V-Presses are highly energy efficient thanks to the rapid stroke technology. This saves time and money



### Economical

Optimised bale dimensions and bale weights for efficient storage, transport and direct commercialisation.



### Automatic start

Automatic start of the pressing process after closing the door.



### Economical, fast and silent

The HSM V-Presses are highly energy efficient thanks to the specially developed rapid stroke technology. This saves time and money.



### Graphic-capable display

Convenient membrane keypad with text display, which shows the current status of the machine.



### HSM TCS

HSM TCS (TorsionControlSystem) for monitoring press ram movement.



### Strapping

Manual bale strapping with Quick-link wire.



[www.tuev-sued.de/ps-zert](http://www.tuev-sued.de/ps-zert)

[www.hsm.eu](http://www.hsm.eu)

**HSM**®