

HSM V-Press 610 P

HSM V-Press 610 P vertical baling press

The vertical baling press is specially designed for the compression of opened or perforated PET/UBC bottles and beverage cans.

Technical data

Order number:	6110204
EAN	4026631083058
Pressing power:	120 kN
Specific pressing power:	25 N/cm ²
Voltage / Frequency:	400 V / 50 Hz
Cycle time when idling vacío:	22 s
Volume throughput in idle operation (theor.):	6,25 m³/h
Loading height:	656 mm
Loading aperture width x height:	800 x 488 mm

Bale length x Bale width x Bale height:	800 x 800 x 600 mm
Noise level (idle operation):	ca. 60 dB(A)
Width x Depth x Height:	1192 x 1058 x 1986 mm
Weight:	540 kg
Related product line:	V-Press
Type of consumables:	Strapping tape
Press material:	PET bottles, aluminium beverage cans, soft packaging, Plastic film, Mixed paper, Cardboard, Punch waste/residue, PET, Getränke und Aluminiumdosen

Product information



Special retaining claws optimize the compression of the pressing material.



Compacts PET and beverage cans



Simple loading thanks to the filling flap at a convenient working height.





Retaining claws

Special retaining claws optimize the compression of the pressing material.



Automatic start

Automatic start of the pressing process after closing the door.



Optimized pressing

Massive press ram and extremely robust press plate guidance.



Graphic-capable display

Convenient membrane keypad with text display, which shows the current status of the machine.



HSM TCS

HSM TCS (TorsionControlSystem) for monitoring press ram movement.



Strapping

Manual bale strapping with continuous polyester tape.



















