HSM VK 7215

Kanalballenpresse HSM VK 7215

Für die professionelle Entsorgungswirtschaft oder größere Industrieanwendungen mit hohen Durchsatzleistungen - Durchsatz bis ca. 498 m³/h

Technical data

Order number:	6445005
Pressing power:	720 kN
Specific pressing power:	87,3 N/cm²
Driving power:	75 kW frequency-controlled
Voltage / Frequency:	400 V / 50 Hz
Cycle time when idling vacío:	8,9 s
Volume throughput in idle operation (theor.):	498 m³/h
Volume throughput at 50kg/m³ (theor.):	24.9 t/h

Loading aperture width x Loading aperture length:	970 x 1500 mm
Bale width x Bale height x Bale length:	1100 x 750 x 600-2000 mm
Length x Width x Height:	10750 x 4159 x 3260 mm
Weight:	24 t
Type of consumables:	Wire
Press material:	Plastic film, Mixed paper, Cardboard, Punch waste/residue, Big Bags, HDPE / LDPE hollow containers & plastic bottles

Product information



Gimballed press cylinder system - Reduced wear on the pressing cylinder and press ram guides



Determining the bale length exactly, even in the case of frequently exchanged material



Available as an option suitable for residual waste (with wear-resistant steel)

Automatic operation

Control of the pressing process via light barrier. Suitable for continuous loading with conveyor belt, air feeding or similar.

Energy efficient

Available as an option with frequency-regulated drive – saves 40 % of the energy used by standard drives.

Optimized transport economy

Optimised bale dimensions and bale weights for efficient truck loading.

Materials

Suitable for cardboard, plastic film and compressing DSD goods, UBC as well as PET bottles (other materials on request).

Bulk weight up to approx. 60 kg/m³

Versatile solution for materials up to approx. 60 kg/m³ bulk weight.

Strapping

Fully automatic 5-fold strapping for optimal bale result also with expansive materials.

Made in Germany

energy efficient

reliabile

www.hsm.eu