



HSM SECURIO B24 document shredder

For increased data security in a modern design. This quiet document shredder with an anti-paper jam function and powerful drive components is designed for continuous operation. We recommend it for use in the workplace.

Technical data

Order number:	1784811	Intake width:	240 mm
EAN	4026631055840	Container volume /	35 l
Cutting type:	particle cut	collecting:	
Cutting size:	1 x 5 mm	Collection volume in sheets (80 g):	626
Security level (DIN 66399):	F-3 P-7	Noise level (idle operation):	ca. 54 dB(A)
Cutting capacity in sheets 80g/m ² :	4	Width x Depth x Height:	395 x 317 x 605 mm
		Weight:	20,5 kg
Power consumption:	610 W		
Voltage / Frequency:	220-240 V / 50 Hz	Shredder material:	Paper

Product information



The induction-hardened, solid steel cutting rollers guarantee durability.



The waste container can be easily removed and emptied.



For convenience, there are castors on the document shredder so it is easy to move around.





For continuous operation

The powerful motor ensures a high cutting capacity and reliable continuous operation.



Energy-saving

In stand-by mode, intelligent control programme EcoSmart ensures there is an exceptionally low power consumption of 0.1 watts.



High level of user safety

The safety element prevents unintentional entry of materials into the machine and thereby increases the user safety.



Automatic start/stop

The operation is very easy: the device starts automatically when fed paper and automatically stops after shredding is complete.



Display bin full

The full bin is indicated via the display and the machine switches off automatically.



Filling level indication

The filling level of the waste container can be seen at all times through the inspection window.

















5 year warranty on the HSM SECURIO B-series document shredders in security levels P-2 to P-5 according to ISO/IEC 21964 (DIN 66399). 3 year warranty on all other HSM SECURIO document shredders. Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).









