

HSM HL 1615



HSM HL 1615 horizontal baling press

This all-purpose stationary baler is designed for high loads and completely flattens paper scraps, large cardboard boxes, plastic foils and comparable materials – even rigid paint cans and light metal barrels (up to 200 litres). To handle even extremely one-sided loads in the press chamber, the press ram guidance has a specially large and sturdy construction. Both large loading flaps, which together function as an oversize feeding opening, make it possible to compact voluminous materials simply and quickly without having to manually tear them into smaller pieces beforehand.

Technical data

Order number:	6219134	Loading aperture width x Loading aperture length:	700 x 1500 mm
EAN	4026631064316	Bale width x Bale height x Bale length:	700 x 800 x 1100 mm
Pressing power:	150 kN	Bale weight:	200 kg
Specific pressing power:	26,78 N/cm ²	Method of loading:	manual
Driving power:	7,5 kW	Length x Width x Height:	4470 x 1343 x 2042 mm
Voltage / Frequency:	400 V / 50 Hz	Weight:	1890 kg
Cycle time when idling vacío:	32 s	Type of consumables:	Strapping tape
Volume throughput in idle operation (theor.):	47 m ³ /h	Press material:	Plastic film, Mixed paper, Cardboard, Getränke und Aluminiumdosen
Loading height:	990 mm		

Product information



Suitable for cardboard as well as film



Compaction against counterplate by horizontal moving press ram



Hydraulic counterplate for bale removal ensures optimum operating convenience and safety



Compact design

Low overall height, large loading aperture, also suitable for bulky material.



Graphic-capable display

Intuitive, multilingual operational guidance via graphic description.



Feeding manual

The extremely large loading aperture makes the unit simple and convenient to load.



Press ram

Compaction against counterplate by horizontal moving press ram.



Automatic bale ready signal

Automatic information as soon as enough material for a bale has been compressed and the bale can be tied.



Strapping

Manual bale strapping with continuous polyester tape.

