



HSM VK 2306

Channel baling press HSM VK 2306

For industrial applications with small material loads - Troughput up to approx. 121 m³/h

Product information

Compresses paper, cardboard, plastic film and PET bottles



Particularly suitable for PET compaction and for special applications



Operating side can be selected



Suitable for continuous loading with conveyor belt, air feeding or similar



Technical data

Order number:	6651002	Bale weight:	140-250 kg
Pressing power:	240 kN	Length x Width x Height:	5295 x 2863 x 1565 mm
Specific pressing power:	64 N/cm ²	Weight:	3,5 t
Driving power:	15 kW	Method of strapping:	horizontal
Voltage / Frequency:	400 V / 50 Hz	Number of strappings:	3
Cycle time when idling:	6,7 s	Type of consumables:	Wire
Volume throughput in idle operation (theor.):	121 m ³ /h	Industry type:	Logistics & Distribution, Food & beverage industry, Industry & Manufacturing, Print & Packaging, Retail
Volume throughput at 50kg/m³ (theor.):	6.05 t/h	Press material:	PET beverage and aluminium cans, soft packaging, Punch waste/residue, PET, Cardboard, Mixed paper, Plastic film
Loading aperture width x Loading aperture length:	670 x 600 mm		
Bale width x Bale height x Bale length:	750 x 500 x 600-1200 mm		