



# HSM VK 2310

## Channel baling press HSM VK 2310

For industrial applications with small material loads - Throughput up to approx. 144 m<sup>3</sup>/h

### Product information

Compresses paper, cardboard, plastic film and PET bottles




Operating side can be selected



Suitable for continuous loading with conveyor belt, air feeding or similar



Loading aperture of 1000 mm suitable for larger material pieces and higher throughput rates



## Technical data

<b>Order number:</b>	6650002	<b>Bale weight:</b>	140-250 kg
<b>Pressing power:</b>	240 kN	<b>Length x Width x Height:</b>	6095 x 2863 x 1940 mm
<b>Specific pressing power:</b>	64 N/cm <sup>2</sup>	<b>Weight:</b>	3,9 t
<b>Driving power:</b>	15 kW	<b>Method of strapping:</b>	horizontal
<b>Voltage / Frequency:</b>	400 V / 50 Hz	<b>Number of strappings:</b>	3
<b>Cycle time when idling:</b>	9,4 s	<b>Type of consumables:</b>	Wire
<b>Volume throughput in idle operation (theor.):</b>	144 m <sup>3</sup> /h	<b>Industry type:</b>	Logistics & Distribution, Industry & Manufacturing, Print & Packaging, Retail
<b>Volume throughput at 50kg/m<sup>3</sup> (theor.):</b>	7.2 t/h	<b>Press material:</b>	PET beverage and aluminium cans, soft packaging, Punch waste/residue, PET, Cardboard, Mixed paper, Plastic film
<b>Loading aperture width x Loading aperture length:</b>	670 x 1000 mm		
<b>Bale width x Bale height x Bale length:</b>	750 x 500 x 600-1200 mm		