

# HSM VK 1206



## Channel baling press HSM VK 2310

For industrial applications with small material loads - Troughput up to approx. 99 m<sup>3</sup>/h

### Product information

System compatible with HSM fully automatic baling systems.



Particularly suitable for cardboard, plastic film and PET bottles



Compresses paper, cardboard, plastic film and PET bottles



Integration into automated industrial production processes



## Technical data

<b>Order number:</b>	6618001	<b>Bale weight:</b>	100-200 kg
<b>Pressing power:</b>	159 kN	<b>Length x Width x Height:</b>	4795 x 2863 x 1565 mm
<b>Specific pressing power:</b>	42,4 N/cm <sup>2</sup>	<b>Weight:</b>	3,4 t
<b>Driving power:</b>	9,2 kW	<b>Method of strapping:</b>	horizontal
<b>Voltage / Frequency:</b>	400 V / 50 Hz	<b>Number of strappings:</b>	3
<b>Cycle time when idling:</b>	8,2 s	<b>Type of consumables:</b>	Wire
<b>Volume throughput in idle operation (theor.):</b>	99 m <sup>3</sup> /h	<b>Industry type:</b>	Logistics & Distribution, Food & beverage industry, Industry & Manufacturing, Print & Packaging, Retail
<b>Volume throughput at 50kg/m<sup>3</sup> (theor.):</b>	4.95 t/h	<b>Press material:</b>	Cardboard, PET beverage and aluminium cans, soft packaging, Punch waste/residue, PET, Mixed paper, Plastic film
<b>Loading aperture width x Loading aperture length:</b>	670 x 600 mm		
<b>Bale width x Bale height x Bale length:</b>	750 x 500 x 600-1200 mm		