# HSM®

Great Products, Great People.

Solutions for industrial and professional Data Destruction

Product Overview

www.hsm.eu

Misuse of data causes millions in damages!

Dealing with files and documents is something you do on a daily basis and everyone is very conscious of the need to act responsibly. However, there is an increase in the occurrence of data leaks which could be detrimental to the reputation of government offices, institutions and companies or lead to financial loss. In today's digital world countless amounts of confidential information are stored on our hard drives, USB sticks, magnetic tapes, CDs, DVDs and Blu-ray discs, credit cards and customer cards as well as discs.

But what happens to these storage devices when they are no longer required?
Many are disposed of carelessly; offered for sale at car boot sales or sold on ebay, the data allegedly having been deleted using conventional wiping routines. This is an open invitation for the data to be misused; it is extremely easy to restore and retrieve confidential data.

These risks can be avoided! HSM offers the largest range of document shredders and digital data media shredders for all areas of application.

O	**T**	**E** SSD	**H**
Optical data carriers	Magnetic data carriers	Electronic data carriers	Electronic data carriers

HSM quality "Made in Germany"

HSM has always adhered to quality principles, whether in development and construction, production, project planning or service. All HSM plants are certified according to DIN EN ISO 9001 and work towards the creation of long-lasting products that retain the value of the HSM brand long into the future.

The clear belief in German production is a part of the responsibility that comes with being an integral element in the regional community. This ensures that every customer can enjoy the high quality of HSM products for a long time.

Made in Germany

We believe that customer satisfaction starts with the advice provided!

- HSM specialists provide you with individual advice on site, even for custom solutions or specific projects. So that you get a system that is specifically tailored to meet your needs.

- We provide advice on data protection to companies and government offices.

Even after your purchase, we are there for you!

- You can rely on our worldwide support as well as on the punctual delivery of spare parts and the processing of service orders.

- HSM service contracts, which include regular maintenance and inspections, ensure operational reliability and security.

The right solution for every security requirement

It only takes a few steps to get the correct security level

1 **Define your protection class ...**

Normal protection requirement for internal data.	High protection requirement for confidential data.	Very high protection requirements for particularly confidential and secret data.
Protection class 1	**Protection class 2**	**Protection class 3**

2 **... which leads to the security levels.**

P-2

Strip width max. 6 mm, approx. 35 pieces*

Internal documents to be rendered illegible or invalidated, for instance internal company communications, such as out-of-date instructions, travel guidelines, notices, forms.

P-3

Particle size max. 320 mm^2, approx. 194 pieces*

Data media with sensitive and confidential data as well as personal data subject to high protection requirements, e.g. company sales reports and tax documents as well as quotations, orders etc. with private address data.

P-4 √GDPR

Particle size max. 160 mm^2, approx. 389 pieces*

Data media with sensitive and confidential data as well as personal data subject to high protection requirements, e.g. balances and conditions as well as payslips, personal data/files, work contracts, tax documents.

P-5 √GDPR

Particle size max. 30 mm^2, approx. 2,079 pieces*

Data media with confidential information of fundamental importance for a person, company or institution, e.g. medical reports, patents, construction documents, strategic papers, competitor analyses, process documentation.

*based on DIN A4, 80 g/m^2

3 **Select the data media relevant for you.**

P

e.g. paper, printed forms

O

e.g. CDs, DVDs, Blu-ray discs

T

e.g. floppy disks, ID cards with magnetic strips

E

e.g. USB sticks, chip cards, solid state drives, flash memory from smartphones

F

e.g. films, foils

HSM shredder baler combinations

HSM Powerline SP 4040 V

This compact combination of the FA 400.2 heavy duty document shredder and a vertical baling press is designed for the professional destruction of large quantities of documents, which are then compressed into bales of up to 35 kg.

- Cutting rollers made of hardened solid steel
- Convenient material feeding via non-slip conveyor belt
- Continuous operation is possible thanks to the powerful motor with a chain drive
- Automatic return eliminates paper jams
- Light barrier for automatic start of the compression process
- Shredded material is compressed into compact bales and can be cleanly disposed of either in a box or waste bag

- Practical removal trolley for the easy removal of bales
- Cross cut shredder baler combinations have a manual oiler
- User safety through emergency off switch
- Functional operator control panel with LED indicator
- Mobile on castors, with parking brake

Max. bale weight / bale size:

35 kg

500 mm
600 mm   400 mm

Model	HSM Powerline SP 4040 V		
Cutting type	Strip cut	Particle cut	Particle cut
Cutting size in mm / Product number	5.8 / 2513111144	5.8 x 50 / 2514111144	3.9 x 40 / 2515111144
Security level ISO/IEC 21964 (DIN 66399)	P-2 / O-2 / T-2 / E-2	P-3 / O-2 / T-3 / E-2	P-4 / O-3 / T-4 / E-3 / F-1
Shredder material			
Cutting capacity in sheets DIN A4 80 g/m²	104	96	80
Cutting speed in mm/s	220	220	220
Intake width in mm	428	428	428
Power consumption in kW	6.2	6.2	6.2
Voltage / Frequency	400 V / 50 Hz	400 V / 50 Hz	400 V / 50 Hz
Dimensions (W x D x H) in mm	1120 x 2175 x 1981	1120 x 2175 x 1981	1120 x 2175 x 1981
Weight in kg	737	737	737
Bale weight max. in kg	35	35	35
Pressing power in kN	44	44	44

HSM shredder baler combinations

HSM Powerline SP 5080

This powerful combination of the FA 500.3 heavy duty document shredder and a counterplate baling press is suitable for data security in archives and compresses the shredded material into bales of between 40 and 80 kg.

- Cutting rollers made of hardened solid steel
- Convenient material feeding via non-slip conveyor belt
- Continuous operation is possible thanks to the powerful motor with a chain drive
- Automatic reverse eliminates paper jams
- Simple commissioning of the combination using Plug-and-Play
- Light barrier for automatic start of the compression process

- Shredder material is compressed into compact bales and can be cleanly disposed of in a waste bag
- The bale weight is variable depending on the requirement
- Automatic oiler provides for consistently high cutting capacity
- User safety through emergency off rail
- Multi-functional element for intuitive operation
- Mobile on castors, with parking brake

Max. bale weight / bale size:

80 kg   490 mm / 570 mm / 800 mm

Model	HSM Powerline SP 5080			
Cutting type	Particle cut	Particle cut	Particle cut	Particle cut
Cutting size in mm / Product number	10.5 x 40-76 / 2992209134	6 x 40-53 / 2990209134	3.9 x 40 / 2994209134	1.9 x 15 / 2993209134
Security level ISO/IEC 21964 (DIN 66399)	P-2 / O-2 / T-2 / E-2	P-3 / O-2 / T-3 / E-2	P-4 / O-3 / T-4 / E-3 / F-1	P-5 / O-3 / T-4 / E-3 / F-1
Shredder material				
Cutting capacity in sheets DIN A4 80 g/m^2	510-550	300-350	180-200	90-100
Cutting speed in mm/s	210	210	210	210
Intake width in mm	500	500	500	500
Power consumption in kW	11.5	11.5	11.5	13.5
Voltage / Frequency	400 V / 50 Hz	400 V / 50 Hz	400 V / 50 Hz	400 V / 50 Hz
Dimensions (W x D x H) in mm	1267 x 2474 x 1792	1267 x 2474 x 1792	1267 x 2474 x 1792	1267 x 2474 x 1792
Weight in kg	1350	1350	1350	1480
Bale weight max. in kg	40-80	40-80	40-80	40-80
Pressing power in kN	80	80	80	80

HSM Powerline SP 5088

With this waste disposal station, HSM combines the FA 500.3 heavy duty document shredder with a channel baling press. It is therefore perfect for use in archives or central stations for shredding large quantities of documents, which are then compressed into bales of up to 90 kg.

- Cutting rollers made of hardened solid steel
- Convenient material feeding via non-slip conveyor belt
- Continuous operation is possible thanks to the powerful motor with a chain drive
- Automatic return eliminates paper jams
- Simple commissioning of the combination using Plug-and-Play
- Light barrier for automatic start of the compression process

- Shredded material is compressed into compact bales, which are manually tied off with three baler straps and can also be disposed of cleanly in a waste bag
- The bale weight is variable depending on the requirement
- Automatic oiler provides for consistently high cutting capacity
- User safety through emergency off rail
- Multifunction element for intuitive operation
- Mobile on castors, with parking brake

Max. bale weight / bale size:

90 kg   500 mm   500 mm   400-950 mm

| Model	HSM Powerline SP 5088		
Cutting type	Particle cut	Particle cut	Particle cut
Cutting size in mm / Product number	10.5 x 40-76 / 2992414134	6 x 40-53 / 2990414134	3.9 x 40 / 2994414134
Security level ISO/IEC 21964 (DIN 66399)	P-2 / O-2 / T-2 / E-2	P-3 / O-2 / T-3 / E-2	P-4 / O-3 / T-4 / E-3 / F-1
Shredder material			
Cutting capacity in sheets DIN A4 80 g/m²	510-550	300-350	180-200
Cutting speed in mm/s	210	210	210
Intake width in mm	500	500	500
Power consumption in kW	11.5	11.5	11.5
Voltage / Frequency	400 V / 50 Hz	400 V / 50 Hz	400 V / 50 Hz
Dimensions (W x D x H) in mm	1273 x 3281 x 1792	1273 x 3281 x 1792	1273 x 3281 x 1792
Weight in kg	1660	1660	1660
Bale weight max. in kg	90	90	90
Pressing power in kN	85	85	85

HSM DuoShredder 5750

Fully automatic two-stage shredder system. Depending on the type of material, a throughput of up to 800 kg/h is achieved. In combination with an HSM baler, the DuoShredder becomes a complete disposal system.

- High quality materials and "Made in Germany" quality for safety and durability
- Multi-level shredder system with two shredding stages. Stage 1: pre-shredding using a four-shaft system consisting of two intake shafts and two cutting shafts; stage 2: pre-shredding using a four-shaft system consisting of two intake shafts and two cutting shafts
- An intelligent level-monitoring feature in the loading hopper optimizes the throughput of the multi-level shredder system with input conveyor belt
- Robust frame construction with integrated, electrically secured inspection and maintenance doors

- Modular construction to save time during installation, servicing and maintenance
- Recommendation: in a space-saving combination with the fully automatic HSM VK12 channel baling press, the TriShredder becomes a complete disposal system.
- The shredder system can also be used for other materials after prior approval by HSM
- Intuitive operating guide with graphics and choice of language
- The system is particularly easy to maintain, shredding stage 2 can be pulled out for better accessibility
- The relevant components are lubricated centrally at an easily accessible point to save time
- The optional monitoring and remote maintenance system ensures continuous operation of the system and minimizes maintenance and down times

Cutting unit stage 1: pre-shredder

Cutting unit stage 2: downstream shredder

Model	HSM DuoShredder 5750	HSM DuoShredder 5750
Cutting type	Particle cut	Particle cut
Cutting size in mm	6 x 40-53	4.6 x 34
Security level ISO/IEC 21964 (DIN 66399)	P-3 / O-2 / T-3 / E-2	P-4 / O-3 / T-4 / E-3 / F-1
Shredder material	🗍 ✎ ▫ 🎚	🗍 ✎ ▫ 🎚
Throughput capacity in kg/h	up to 800	up to 650
Working width in mm	500	500
Power consumption in kW	1st stage= 2 x 5.5 / 2nd stage = 2 x 5.5	1st stage = 2 x 5.5 / 2nd stage = 2 x 5.5
Dimensions (W x D x H) in mm*	1900 x 1200 x 3300	1900 x 1200 x 3300

*depending on project-related design

HSM TriShredder 6060

Fully automatic multi-level shredder system with three cutting units and a throughput of up to 2500 kg/h. In combination with an HSM baler, the TriShredder becomes a complete disposal system.

- High quality materials and "Made in Germany" quality for safety and durability
- Multi-level shredder system with three shredding stages
- Stage 1: pre-shredding using a four-shaft system consisting of two intake shafts and two cutting shafts
- Stages 2 and 3: fine shredding using a two-shaft system
- An intelligent level-monitoring feature in the loading hopper optimizes the throughput of the multi-level shredder system with input conveyor belt
- Robust frame construction with integrated, electrically secured inspection and maintenance doors
- Modular construction to save time during installation, servicing and maintenance
- Plug-and-play connections for easy commissioning of the shredder system
- Recommendation: in a space-saving combination with the fully automatic HSM VK23 channel baling press, the TriShredder becomes a complete disposal system

- The shredder system can also be used for other materials after prior approval by HSM
- Intuitive operating guide with graphics and choice of language
- A metal separator is available as an option to ensure cleanly sorted shredded material and to protect shredding stage 3 from metal pieces
- Optionally available electrical extension mechanism for the 2nd and 3rd shredding stages to set the required fragment size for the shredded material
- The relevant components are lubricated centrally at an easily accessible point to save time
- The optional monitoring and remote maintenance system ensures continuous operation of the system and minimizes maintenance and down times

Model	HSM TriShredder 6060	HSM TriShredder 6060
Cutting type	Particle cut	Particle cut
Cutting size in mm	7.5 x 40-80	4.6 x 34
Security level ISO/IEC 21964 (DIN 66399)	P-3 / O-2 / T-3 / E-2	P-4 / O-3 / T-4 / E-3 / F-1
Shredder material	🗍 ✎ ▭ 💾	🗍 ✎ ▭ 💾
Throughput capacity in kg/h	up to 2500	up to 2000
Working width in mm	650	650
Power consumption in kW	1st stage: 2 x 11 2nd stage: 2 x 11 3rd stage: 2 x 11	
Dimensions (W x D x H) in mm*	1940 x 1430 x 3900	1940 x 1430 x 3900

*depending on project-related design

HSM StoreEx OMDD 130

HSM StoreEx HDS 150

HSM digital data media shredders

HSM StoreEx OMDD 130

Dieser Medienvernichter ist speziell für die Zerkleinerung von CDs/DVDs und Kunden-/Kreditkarten bei höchsten Sicherheitsanforderungen ausgelegt.

- High quality materials and "Made in Germany" quality for safety and durability.
- Cutting rollers made of hardened solid steel.
- Powerful, energy-saving power unit enables long operation.
- High degree of energy saving due to stand-by.
- The device automatically switches off if pressure is applied to the safety element. Safety element prevents unintentional entry and serves as a splinter shield.
- Light barrier for automatic start/stop.
- An automatic reverse rectifies material jams.
- Optical display and shut down if the bin is full.
- Can be moved on castors.

HSM StoreEx HDS 230

Secure, data protection compliant and economical. This digital data media shredder shreds digital data carriers into little particles and makes data recreation virtually impossible.

- High quality materials and "Made in Germany" quality for safety and durability
- Powerful, energy-saving power unit enables long operation
- Convenient operation via the membrane keypad with display
- LED display for continuous input of media at a comfortable working height
- Different functional modes for the various types of material and maximum throughput
- Time-saving direct input of CDs/loyalty cards
- Removable waste container / discharge conveyor belt on the right or left (depending on model)
- Low maintenance due to closed direct drive unit

Model	HSM StoreEx OMDD 130	HSM StoreEx HDS 150
Cutting type	Particle cut	Particle cut
Type	single-stage	single-stage
Cutting size in mm	2.2 x 4	40
Shredder material	🖴 ▪ 🗔	🖴 🖴 🖴 ▪ 🗔
Cutting capacity in items/hr	up to 2000 CDs/DVDs (1 item per pass)	up to 1200 hard drives 2.5", up to 210 hard drives 3.5" (1 item per pass); up to 4200 CDs/DVDs; up to 280 magnetic tapes
Security level ISO/IEC 21964 (DIN 66399)	O-5 / T-6 / E-5	H-3 / T-1 / T-2
Voltage / Frequency	220-240 V / 50/60 Hz	220-240 V / 50/60 Hz
Power consumption in kW	1.9 / -	- / 1.5
Weight in kg	91	534
Dimensions (W x D x H) in mm	620 x 487 x 1021	1200 x 815 x 1325
Dimensions of feed-in opening (B x T x H) in mm	-	165 x 290 x 60

HSM StoreEx HDS 230
with removable waste container

HSM StoreEx HDS 230
with discharge conveyor belt

HSM StoreEx HDS 230

Secure, data protection compliant and economical. This digital data media shredder shreds digital data carriers into little particles and makes data recreation virtually impossible.

- High quality materials and "Made in Germany" quality for safety and durability
- Powerful, energy-saving power unit enables long operation
- Convenient operation via the robust membrane keypad with display
- The large LED display enables the continuous input of media at a comfortable working height
- Different functional modes for the various types of material and maximum throughput
- Time-saving direct input of CDs/loyalty cards
- Removable waste container for effortless emptying (depending on model)
- Low maintenance due to closed direct drive unit

Model	HSM StoreEx HDS 230	HSM StoreEx HDS 230
Cutting type	Strip cut	Particle cut
Type	single-stage	dual-stage
Cutting size in mm	20 x 40-50 (< 1000 mm^2)	11.5 x 26 (< 300 mm^2)
Shredder material	🔘 🎵 💿 ▪ 📇	🔘 🎵 💿 ▪ 📇
Cutting capacity in items/hr	up to 1500 hard drives 2.5", up to 360 hard drives 3.5" (1 item per pass); up to 7500 CDs/DVDs; up to 500 magnetic tapes	up to 1150 hard drives 2.5", up to 280 hard drives 3.5" (1 item per pass); up to 6000 CDs/DVDs; up to 420 magnetic tapes
Security level ISO/IEC 21964 (DIN 66399)	H-4 / O-1 / T-2 / E-2	H-5 / O-2 / T-3 / E-2
Voltage / Frequency	3 x 400 V / 50 Hz	3 x 400 V / 50 Hz
Power consumption in kW	3	6
Weight in kg	733	1098
Dimensions (W x D x H) in mm	1550 x 870 x 1420 (model with removable waste container) 2850 x 870 x 1716 (model with discharge conveyor belt)	
Dimensions of feed-in opening (B x T x H) in mm	165 x 300 x 60	165 x 300 x 60

● **Head office and production sites in Germany**

○ **Subsidiaries**

● **Sales and service points**

HSM GmbH + Co. KG
Austraße 1-9
88699 Frickingen / Germany
Tel. + 49 7554 2100-0
Fax + 49 7554 2100-160
info@hsm.eu
www.hsm.eu

HSM Técnica de Oficina y
Medioambiente España, S.L.U.

HSM France SAS

HSM (UK) Ltd.

HSM Polska Sp. z o.o.

HSM of America LLC

All specifications are listed without guarantee. Technical and design modifications reserved.
For latest product specifications visit www.hsm.eu

10/2024 – W52282